



Motor Drive and Motor Control

Category: Electrical Engineering · Model reference: MZM-4018



SPECIFICATIONS

1. MZM-4022/1 - AC MOTOR 1.5HP 230V 50HZ

TECHNICAL SPECIFICATION :

1. Capacitor Start Induction Motor

- Voltage : 230V AC, Single Phase, 50Hz
- Power : 1.1kW (1.5 HP)
- Speed : 1200~1500 r.p.m / 4 pole
- Mounting : Class B (foot mounting)
- Temperature rise : 70° ~ 90° C
- Frame and Cooling : Totally enclosed fan cooled (TEFC)

2. Capacitor Start and Capacitor Run Induction Motor

- Voltage : 230V AC, single phase, 50Hz
- Power : 1.1kW (1.5HP)
- Speed : 1200 ~ 1500 r.p.m / 4 pole
- Mounting : Class B (foot mounting)
- Temperature rise : 70° ~ 90° C
- Frame and Cooling : Totally enclosed fan cooled (TEFC)

2. MZM-4022/2 - SLIP RING INDUCTION MOTOR 3 PHASE 400V 50 HZ

TECHNICAL SPECIFICATION :

- Voltage : 415VAC, Three-phase, 50Hz
- Power : 15HP
- Output speed : 1500 rpm/4 Pole
- Frame and Cooling : Drip-proof / totally enclosed for cooled (TEFC)
- Mounting : Foot mounting
- Insulation Class : Class F or better
- Temperature rise : 80°C

3. MZM-4022/3 - SQUIRREL CAGE INDUCTION MOTOR 3HP 3PHASE 400V 50HZ

TECHNICAL SPECIFICATION :

- 1. Voltage : 400VAC, Three Phase, 50Hz

- 2. Power : 3HP

- 3. Output speed : 1500 rpm / 4 Pole

- 4. Frame and Cooling : Drip/proof / totally enclosed for cooled (TEFC)

- 5. Mounting : Foot Mounting

- 6. Insulation Class : Class F

- 7. Temperature rise : Max 80°C

- 8. Come with single motor portable base and castor wheels

4. MZM-4022/4 - SQUIRREL CAGE INDUCTION MOTOR 5HP 3PHASE 400V 50HZ

TECHNICAL SPECIFICATION :

- 1. Voltage : 400VAC, Three Phase, 50Hz

- 2. Power : 5HP

- 3. Output speed : 1500 rpm / 4 Pole

- 4. Frame and Cooling : Drip/proof / totally enclosed for cooled (TEFC)

- 5. Mounting : Foot Mounting

- 6. Insulation Class : Class F

- 7. Temperature rise : Max 80°C

- 8. Come with single motor portable base and castor wheels

5. MZM-4022/5- SQUIRREL CAGE INDUCTION MOTOR 3PHASE 10HP 400V 50HZ

TECHNICAL SPECIFICATION :

- 1. Voltage : 400VAC, Three Phase, 50Hz

- 2. Power : 10HP

- 3. Output speed : 1500 rpm / 4 Pole

- 4. Frame and Cooling : Drip/proof / totally enclosed for cooled (TEFC)

- 5. Mounting : Foot Mounting

- 6. Insulation Class : Class F

- 7. Temperature rise : Max 80°C

- 8. Come with single motor portable base and castor wheels

Send Enquiry **Your Name**

Your Email

Tele Phone