



Safety Modular Tranformer

Category: Electrical Engineering · Model reference: MZM-4023



SPECIFICATIONS

SAFETY MODULAR TRANSFORMER

Features :

- Both primary coil and secondary coil has safety cover
- Primary circuit has standard power socket, fuse and switch
- Secondary circuit has 4 mm safety socket and double isolation

UNITS

PRIMARY COIL MDT-P1 - 220V power supply - 440T, Max.I 4A - Power socket, switch, fuse - Dimension: 110x90x100mm - Weight: 0.85kg	MDT-P1
PRIMARY COIL MDT-P2 - 110V power supply - 220T, Max.I 8A - Power socket, switch, fuse - Dimension: 110x90x100mm - Weight: 0.85kg	MDT-P2
SECONDARY COIL MDT-S1 - Consists of 5 windings in series - 6T, 12T, 24T, 48T, 96T - Max.I 25A, 25A, 13A, 6.6A, 3.3A - 4 mm safety socket output - Double isolation - Dimension: 110x90x100mm - Weight: 0.85kg	MDT-S1
SECONDARY COIL MDT-S2 - Consists of 2 windings in series - 1000T, 1000T, Max.I 0.8A - Warning: w/o load, the coil delivers 1000V - 4 mm safety socket output - Double isolation - Dimension: 110x90x100mm - Weight: 0.85kg	MDT-S2
SECONDARY COIL MDT-S3 - Consists of 2 windings in series - 220T, 220T, Max.I 3.6A - Warning: w/o load, the coil delivers 220V - 4 mm safety socket output - Double isolation - Dimension: 110x90x100mm - Weight: 0.85kg	MDT-S3
SECONDARY COIL MDT-S4 - Consists of 2 separate coils and each coil has 2 symmetrically windings - 12T, 12T, 24T, 24T - Max.I 25A, 13A - 4 mm safety socket output - Double isolation - Dimension: 110x90x100mm - Weight: 0.85kg	MDT-S4

Send Enquiry **Your Name****Your Email****Tele Phone**



MZFIRSTMOTION SDN BHD · Reg No. 1137962-V · No 53, Lorong 1/SS3, Bandar Tasek Mutiara, 14120 Simpang Ampat, Pulau PinangT: +604-505 7422 · E: sales@mzfirstmotion.com · <https://www.mzfirstmotion.com>