



Single & Three Phase Load

Category: Electrical Engineering · Model reference: MZM-4024



SPECIFICATIONS


SINGLE & THREE-PHASE LOAD Features - Steps of 20% - DC mode or 220V(50Hz) single phase - Three-phase star 380V(50Hz) and delta 220V(50Hz)					
MZM-4028-1					
Model	Power	Resistor	Dimensions (W×H×D) mm	Weight (kg)	Phase
MZM-4028-1	200W/400W/600W 800W/1000W	242Ω/121Ω/81Ω 61Ω/48Ω	200×250×425	8	Single
MZM-4028-2	(200W/400W/600W 800W/1000W)×3	(242Ω/121Ω/81Ω 61Ω/48Ω)×3	400×250×425	24	Three
MZM-4028-3					
Model	Power	Capacitor	Dimensions (W×H×D) mm	Weight (kg)	Phase
MZM-4028-3	200W/400W/600W 800W/1000W	13μF/26μF/39μF 53μF/66μF	150×130×185	1.5	Single
MZM-4028-4	(200W/400W/600W 800W/1000W)×3	(13μF/26μF/39μF 53μF/66μF)×3	300×130×185	3	Three
MZM-4028-5					
Model	Power	Inductor	Dimensions (W×H×D) mm	Weight (kg)	Phase
MZM-4028-5	200W/400W/600W 800W/1000W	770mH/385mH/257mH 193mH/154mH	190×150×365	10	Single
MZM-4028-6	(200W/400W/600W 800W/1000W)×3	(770mH/385mH/257mH 193mH/154mH)×3	380×150×365	30	Three

Cooling Fan MZM-4028-2

MZM-4028-4

MZM-4028-6

 Send Enquiry **Your Name**
Your Email
Tele Phone



MZFIRSTMOTION SDN BHD · Reg No. 1137962-V · No 53, Lorong 1/SS3, Bandar Tasek Mutiara, 14120 Simpang Ampat, Pulau PinangT: +604-505 7422 · E: sales@mzfirstmotion.com · <https://www.mzfirstmotion.com>