



TPR-3005-2D

Category: Test & Measurement · Model reference: MZM-9015



SPECIFICATIONS

DESCRIPTION

Input voltage: AC220V $\pm$ 10%,50Hz $\pm$ 2Hz;AC220V-5%,50Hz $\pm$ 2Hz

Two-way regulated power supply

Rated output voltage: 2x0-30V

Rated output current: 2x0-5A

Current effect: CVLoad effect: CVRipples and noises:

CVProtection: Current limiting protection

Instruction

Digital voltmeter and ammeter,three digital displays Precision: voltmeter $\pm$ 1%,+2 figures; Ammeter $\pm$ 2%,+2 figures

Regular output power supply

Nominal output voltage: 5V $\pm$ 3%

Nominal output current: 3A

Current effect: Load effect: Ripples and noises: Protection: Current limitation and protection for short circuit

1. Quad Independent DC Output

2. Four LED Display with 3 digits, selectable for two sets output voltage and current display.

3. 2 Output 90W Adjustable Bench Top DC Power Supply with 3 Digits

4. LED Display Auto series, parallel and tracking operation.

5. Constant voltage and constant current operation.

6. Low ripple and noise.

7. Overload and reverse polarity protection

8. Selectable for continuous / dynamic load

9. Output enable / disable control

10. Rotation speed of the fan is controlled by heat sink temperature

- Environmental conditions:0-40Celsius;<90%

- Working hours: constantly

- working more than 8 hours

- Display mode: pointer display

Send Enquiry **Your Name**

Your Email

Tele Phone

